

Product sheet

Basic Information

Order Number
Type
Common Number



1450000320
E-17172
P4536



8592920085646

Measuring Unit
Packaging
Net Weight [kg]
Dimensions [mm]
Technical Support

KS
1 / - / 4 / 8
0.976
85 × 235 × 195
Tomáš Pořízek, 581261141,
porizek@emos.cz



5 lighting
modes

Technical Description

source of light
maximal light output
light output
maximal beam distance
beam distance
number of lighting modes
lighting modes
runtime
runtime detail
impact resistance

2× COB LED
2 000 lm
2× COB LED 100 % – 2 000 lm, 2× COB LED 50 % – 1 000 lm, 1× COB LED 100 % – 1 000 lm, 1× COB LED 50 % – 500 lm, 1× COB LED 25 % – 250 lm
70 m
2× COB LED 100 % – 70 m, 2× COB LED 50 % – 45 m, 1× COB LED 100 % – 45 m, 1× COB LED 50 % – 35 m, 1× COB LED 25 % – 25 m
5
2× COB LED 100 %, 2× COB LED 50 %, 1× COB LED 100 %, 1× COB LED 50 %, 1× COB LED 25 %
3.5–14.5 hrs
2× COB LED 100 % – 3.5 hrs, 2× COB LED 50 % – 5.5 hrs, 1× COB LED 100 % – 5.5 hrs, 1× COB LED 50 % – 8.5 hrs, 1× COB LED 25 % – 14.5 hrs
yes

Product sheet

Rechargeable COB LED Work Floodlight P4536, 2000 lm, 8000 mA

waterproof	no
rechargeable	yes
battery	Li-Ion accumulator
battery type	8 000 mAh/3.7 V
batteries included	yes
recharge time	7 hrs
power connector type	USB C
LED indication of the charging process	yes
LED indication of the accumulator state	yes
special features	quick switch ON/OFF, battery protection
features	swivel handle, 4× magnet
accessories	USB cable
material	ABS plastic + rubber
colour	black-green
dimensions	214 × 140 (280) × 56 mm
weight	818 g
packaging	1 pc, box
warranty period	2 years