



205.W119-T

WALL BOX CABLE+SOCKET T2

Type 2 3P+N+E 16A 400V~ 11kW 16A 400V
3P+N+E IP55 IK08 Type 2 5m

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Product type	WALL BOX CABLE+SOCKET T2	IEC 61439-7 (2018)	[International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations
Commercial series	BE-W[2.0] Series		
Synthetical description	WALL BOX CABLE+SOCKET T2	EN IEC 61851-1 (2019)	[European Standard] Electric vehicle conductive charging system - Part 1: General requirements
Material	ENGINEERING PLASTIC	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
EV standard	Type 2 3P+N+E 16A 400V~ 11kW	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
With integrated cable	Type 2		
Cable length	5m		
Cable section	5G2,5+1x0,5mm ²		
Rated current	16A		
Rated voltage	400V		
Working frequency	50/60Hz		
Poles	3P+N+E		
Protection degree IP	IP55		
Working temperature	-30°C/+50°C		
GLOW WIRE	GW 650°C		
Protection degree IK	IK08		
Colour	ANTHRACITE		

Mounting version	SURFACE MOUNTING
Dimensions	235x370x115mm
EV functions	N/A
EV functions	PREDISP. FOR SERIAL COMMUN.
EV functions	WORKING IN MODE STD-ALONE FREE
EV functions	PWR CONTACTOR APERTURE MONIT.
EV functions	CHARGE MODE 3 WITH PWM C.PILOT
EV functions	EN. MET. AND CURRENT CONSUMP.
EV functions	N/A
EV functions	N/A
EV equipment	1 DC LEAKAGE DETECTOR
EV equipment	1 RBG LED STRIPES
EV equipment	1 POWER SUPPLY 24VDC 36W
EV equipment	N/A
EV equipment	1 FUSE HOLDER 1P+N GG 4A
EV equipment	1 MOD. CONTACT. 4P 25A 24VDC
EV equipment	1 TERMINAL STRIP 5X10MM ²
EV equipment	N/A
EV equipment	1 DIGIT. ENERGY METER 3P+N 80A
EV equipment	1 CABLE HOLDER IN TECHNOPOLYM.
EV excluded	1 CI.BRK. 3P+N C20 30MA IST. A
EV excluded	1 SHUNT TRIP RELEASE 24VDC
EV excluded	UPSTREAM PROTECTI. (BY INST.)
EV specifications	205.W119-T