




Product data sheet

HDC32511M7

Characteristics

Contactor, HDC3-2511, 220/230 V, 50/60 Hz



Main

|                                             |               |
|---------------------------------------------|---------------|
| Range of product                            | HDC3          |
| Product or component type                   | Contactor     |
| Contactor application                       | Non-reversing |
| Poles description                           | 3P            |
| [Ith] conventional free air thermal current | 40 A          |

Complementary

|                                |                                                                                                          |
|--------------------------------|----------------------------------------------------------------------------------------------------------|
| Utilisation category           | AC-3<br>AC-4                                                                                             |
| [In] rated current             | 25 A                                                                                                     |
| [Uc] control circuit voltage   | 220/230 V AC 50/60 Hz                                                                                    |
| Auxiliary contact composition  | 1 NO + 1 NC                                                                                              |
| [Ui] rated insulation voltage  | 690 V                                                                                                    |
| [Ie] rated operational current | 25 A at 380/400 V AC-3<br>18 A at 660/690 V AC-3<br>8.5 A at 380/400 V AC-4<br>4.4 A at 660/690 V AC-4   |
| Motor power kW                 | 11 kW at 380/400 V AC-3<br>15 kW at 660/690 V AC-3<br>5.5 kW at 380/400 V AC-4<br>4 kW at 660/690 V AC-4 |

Environment

|                                               |                                                |
|-----------------------------------------------|------------------------------------------------|
| Installation category                         | III                                            |
| Pollution degree                              | 3                                              |
| Ambient air temperature for operation         | -5...40 °C                                     |
| Average ambient air temperature for operation | = 35 °C (average over 24 hours)                |
| Ambient air temperature for storage           | -25...55 °C                                    |
| Operating altitude                            | 2000 m                                         |
| Standards                                     | IEC 60947-4-1                                  |
| Product certifications                        | CB<br>CE<br>SEMKO                              |
| IP degree of protection                       | IP20                                           |
| Relative humidity                             | 0...50 % at 0...40 °C<br>0...90 % at 0...20 °C |