



Product data sheet

HDM3S160M160B3XX

Characteristics

Molded case circuit breaker, HDM3S, 160M, 160A 4P, TM, adjustable, 40?

|                                                                                    |                           |                                                                                                             |
|------------------------------------------------------------------------------------|---------------------------|-------------------------------------------------------------------------------------------------------------|
|  | Main                      |                                                                                                             |
|                                                                                    | Range of product          | HDM3S                                                                                                       |
|                                                                                    | Product or component type | Enclosed moulded case circuit breaker                                                                       |
|                                                                                    | Frame size                | 160AF                                                                                                       |
|                                                                                    | Suitability for isolation | Yes                                                                                                         |
|                                                                                    | Trip unit technology      | Thermal-magnetic                                                                                            |
|                                                                                    | Device application        | Power distribution protection                                                                               |
|                                                                                    | Voltage release type      | Shunt trip release<br>Undervoltage release                                                                  |
|                                                                                    | Provided equipment        | alarm<br>motor mechanism<br>handle<br>terminal extension<br>interphase barriers<br>MN or MX voltage release |
|                                                                                    |                           |                                                                                                             |

Complementary

|                                        |                |
|----------------------------------------|----------------|
| Poles description                      | 4P             |
| [In] rated current                     | 160 A          |
| [Ue] rated operational voltage         | 400/415 V      |
| Network type                           | AC             |
| Network frequency                      | 50/60 Hz       |
| Electrical durability                  | 1500 cycles    |
| Mechanical durability                  | 8500 cycles    |
| [Uimp] rated impulse withstand voltage | 8.0 kV         |
| [Ics] rated service breaking capacity  | 35 kA at 400 V |
| Rated breaking capacity                | 35 kA at 400 V |
| [Ui] rated insulation voltage          | 1000 V         |
| Clamping connection capacity           | 70 mm²         |
| Utilisation category                   | Category A     |
| Height                                 | 155 mm         |
| Width                                  | 120 mm         |
| Depth                                  | 108 mm         |

Environment

|                                       |            |
|---------------------------------------|------------|
| IP degree of protection               | IP20       |
| Installation category                 | III        |
| Pollution degree                      | 3          |
| Ambient air temperature for operation | -5...40 °C |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                                     |             |
|-------------------------------------|-------------|
| Ambient air temperature for storage | -20...70 °C |
| Operating altitude                  | 0...2000 m  |
| Standards                           | IEC 60947-2 |
| Product certifications              | TÜV         |

Packing Units

|                              |     |
|------------------------------|-----|
| Unit Type of Package 1       | PCE |
| Number of Units in Package 1 | 1   |