

Product data sheet

HLAY5BJ33

Characteristics

Selector switch, HLAY5, 2NO, 3 positions +/- 45, stay put, long handle, black



Main

| Range of product | HLAY5 |
|---------------------------|------------------|
| Device presentation | Complete product |
| Product or component type | Selector switch |
| Bezel material | Metal |
| Mounting diameter | 22 mm |
| Head type | Standard |

Complementary

| Fixing collar material | Metal |
|---|--|
| Cap/operator or lens colour | Black |
| Shape of signaling unit head | Round |
| Type of operator | Stay put |
| Operator profile | Black long handle |
| Operator position information | 3 positions +/- 45° |
| Contacts type and composition | 2 NO |
| Contact operation | Slow-break |
| Contacts usage | Standard contacts |
| Mechanical durability | 100000 cycles |
| Connections - terminals | Screw clamp terminals |
| [Ith] conventional free air thermal current | 6 A |
| [Uimp] rated impulse withstand voltage | 6 kV |
| [Ie] rated operational current | 2 A at 380 V 3.3 A at 220 V, AC-15 0.5 A at 220 V 1.1 A at 110 V, DC-13 |
| Electrical durability | 50000 cycles |
| E-commerce address | Hlay5-selector-switches-with-handle |

Environment

| Ambient air temperature for operation | -540 °C |
|---------------------------------------|---------------|
| Standards | IEC 60947-5-1 |