



Product data sheet

HLAY5BS442

Characteristics

Emergency stop pushbutton, HLAY5, mushroom 30 mm, 1 NC, red



Main

| | |
|---------------------------|----------------------------|
| Range of product | HLAY5 |
| Device presentation | Complete product |
| Product or component type | Emergency stop push-button |
| Mounting diameter | 22 mm |
| Head type | Standard |

Complementary

| | |
|---|--|
| Fixing collar material | Metal |
| Cap/operator or lens colour | Red |
| Shape of signaling unit head | Round |
| Reset | Turn to release |
| Operator profile | Red mushroom Ø 30 mm |
| Contacts type and composition | 1 NC |
| Contact operation | Slow-break |
| Contacts usage | Standard contacts |
| Mechanical durability | 100000 cycles |
| Connections - terminals | Screw clamp terminals |
| [Ith] conventional free air thermal current | 6 A |
| [Uimp] rated impulse withstand voltage | 6 kV |
| [Ie] rated operational current | 2 A at 380 V 3.3 A at 220 V, AC-15 0.5 A at 220 V 1.1 A at 110 V, DC-13 |
| Electrical durability | 50000 cycles |
| E-commerce address | Hlay5-pushbuttons-mushroom-and-emergency-stop-pushbuttons-1 |

Environment

| | |
|---------------------------------------|------------------------------------|
| Ambient air temperature for operation | -5...40 °C |
| IP degree of protection | IP40 IP65 with protective cover |
| Standards | IEC 60947-5-1 |