



Product data sheet

HLAY5BW84M5L

Characteristics

Illuminated double-headed push-button, HLAY5, 1 NO + 1 NC, 1 flush - 1 projecting push-buttons - 1 central pilot light



Main

Range of product	HLAY5
Device presentation	Complete product
Product or component type	Illuminated double-headed push-button
Bezel material	Metal
Mounting diameter	22 mm
Head type	Standard
Light source	LED

Complementary

[Us] rated supply voltage	220 V
Cap/operator or lens colour	Green + yellow + red
Fixing collar material	Metal
Shape of signaling unit head	Rectangular
Type of operator	Spring return
Operator profile	Green flush, I Red projecting, O
Operator profile	1 flush - 1 projecting push-buttons - 1 central pilot light
Contacts type and composition	1 NO + 1 NC
Contact operation	Slow-break
Contacts usage	Standard contacts
Mechanical durability	100000 cycles
Connections - terminals	Screw clamp terminals
[Ith] conventional free air thermal current	6 A
[Uimp] rated impulse withstand voltage	6 kV
[Ie] rated operational current	2 A at 380 V 3.3 A at 220 V, AC-15 0.5 A at 220 V 1.1 A at 110 V, DC-13
Electrical durability	50000 cycles
Signalling type	Steady
E-commerce address	Hlay5-illuminated-pushbuttons-with-flush-push-led-1

Environment

Ambient air temperature for operation	-5...40 °C
IP degree of protection	IP40 IP65 with protective cover

