

XSOLIS IP67

SLS02FC8IP

ARELUX S.R.L.
Alexei Tolstoy street, nr. 12, Bacău - 600093, ROMÂNIA.
Tel: +40 0234 514 492 / 546 620. Fax: +40 0234 546 677.

www.arelux.ro

05/2024

General information / Informații generale / Informazioni generali

Operating temperature **-10 ÷ +50 °C**



Description / Descriere / Descrizione

EN - Flexible (with 2P cable, 180 mm) connecting element for XSOLIS IP67, 24V DC LED strips, 8 mm width of PCB, 50 pcs. / bag Sealing during installation is done with the help of liquid silicone.

RO - Element de conexiune flexibilă (cu cablu 2P, 180 mm), pentru benzile cu LED-uri XSOLIS IP67, 24V DC, grosime PCB 8 mm, 50 buc. / pungă. Realizarea etanșării la montaj se realizează cu ajutorul siliconului lichid.

IT - Connettore flessibile (con cavo 2P, 180 mm) per strisce LED XSOLIS IP67, 24 V DC, larghezza del PCB 8 mm, 50 pezzi / sacchetto. La sigillatura durante l'installazione deve essere eseguita con l'aiuto di silicone liquido.



**5 YEARS
WARRANTY**